

Auri In 6W

2044
empotrado recessed

500Lm~600Lm / 2700K~4000K

IP20 / CRI ≥ 90 / 20° 40° 60°

HER

Light Lovers.



DESCRIPCIÓN DESCRIPTION

Luminaria semi-empotrada de líneas curvas y suaves.

Circular tilting semi-recessed luminary. It projects light with curves and soft lines.

REFERENCIAS REFERENCES

Model	Color Temperature	Lumen	Efficiency
2044/27	2700K	500Lm	83,3Lm/W
2044/30	3000K	550Lm	91,7Lm/W
2044/40	4000K	600Lm	100Lm/W

GENERAL

negro black customizable custom
empotrado recessed
IP20
IK07

APARATO DE ILUMINACIÓN LIGHTING FIXTURE

20° 40° 60°
IRC ≥ 90 CRI ≥ 90
IP20
MacAdam ≤ 3
UGR <19
difusor transparente
clear diffuser
valores de potencia del sistema (LED + driver): 6,6W
power values of the system (LED + driver): 6,6W

ACCESORIOS ACCESSORIES

FL025 Filtro escultura 25°-37°
FL060 sculpture filter 25°-37°
FL030 Filtro escultura 21°-30°
FL060 sculpture filter 21°-30°
FL035 Panel de abeja
FL035 honeycomb diffuser
FL045 Cristal transparente
FL060 frosted glass
FL050 Cristal glaseado
FL050 transparent glass

ELÉCTRICA ELECTRICAL

6W
220-240VAC 50/60Hz
equipo incluido
gear included

MEDIDAS MEASURES







Ø80mm

REGULACIÓN DIMMING

on / off
corte de fase IGBT/TRIAC
phase-cut dimming IGBT/TRIAC
1-10V
pulsador
push
DALI

RECORTE CUTOUT

Ø43mm
min. espesor del techo: 13mm
min. ceiling thickness: 13mm
máx. espesor del techo: 40mm
max. ceiling thickness: 40mm
profundidad empotrada: 45mm
recessed depth: 45mm



cambio sin previo aviso change without notice